

TOSHIBA

Leading Innovation >>>

Providing a full line of cameras, recorders,
software and accessories for your

IP Video Surveillance Systems


2015-2016 Catalog



Overview of Recording Solutions for 2015-2016

MODEL	EAV16-480	XVSV	XVSE	DVSE	IPSE	NVSPRO
PLATFORM	Surveillix	Surveillix	Surveillix	Surveillix	Surveillix	Surveillix
IP only	Analog	-	-	-	Y	Y
Hybrid	-	Y	Y	Y	-	-
Local viewing	Y	Y	Y	Y	Y	Y
VMS software	SCS	SCS	SCS	SCS	SCS	SCS
Mobile app (Android, iPhone, iPad)	Y	Y	Y	Y	Y	Y
Mac app (Search & Live)	Y	Y	Y	Y	Y	Y
Expandable to 64 IP channels	-	Y	Y	Y	Y	Y
Max storage	12TB	12TB	18TB	24TB	18TB	96TB
RAID**	-	-	-	RAID5	-	RAID5
Removable hard drives	-	-	-	Y	-	Y
Channels	16	16	16	8-32	8-32	8-64
Windows 7 OS	-	Y	Y	Y	Y	Y
Embedded Linux OS	Y	-	-	-	-	-
Built-in PoE switch	-	-	-	-	-	-
Max IP throughput** (Mbps)	NA	200	200	200 (Non-RAID) 400 (RAID5)	200	200 (Non-RAID) 400 (RAID5)
ONVIF	-	Profile-S	Profile-S	Profile-S	Profile-S	Profile-S

* Single channel only
 ** RAID configuration is optional and may incur additional costs



All Toshiba recording solutions come with FREE software for life of recorder with no annual software fees providing low total cost-of-ownership (TCO).

Overview of IP Cameras for 2015-2016

MODEL	IK-WF51A IK-WF51R	IK-WD31A IK-WR31A	IK-WD14A IK-WR14A	IK-WD05A IK-WR05A	IKS-WR7412	IKS-WD6112	IK-WD04A IK-WR04A	IK-WB81A	IKS-WP8103 IKS-WP8203R	IKS-WR7022
Resolution	5MP Panoramic	3MP	1080p	1080p	1080p	1080p	720p	1080p	3MP	1080p
Compression	H.264, MPEG4, MJPEG	H.264 Smart Codec	H.264, MPEG4, MJPEG	H.264, MPEG4, MJPEG	H.264, MPEG4	H.264, MJPEG	H.264, MPEG4, MJPEG	H.264, MPEG4, MJPEG	H.264, MJPEG	H.264, MJPEG, MPEG4
Frame rate	15, 25, 30 FPS	20, 30, 60 FPS	30 FPS	30 FPS	30 FPS	30 FPS	30 FPS	30 FPS	30 FPS	30 FPS
Application	Indoor Outdoor *1, *2	Indoor Outdoor *1, *2	Indoor Outdoor *1, *2	Indoor Outdoor *1, *2	Outdoor *2	Indoor	Indoor Outdoor *1, *2	Outdoor *2	Indoor Outdoor *2	Indoor Outdoor *2
Min. illumination (B&W)	0.0 lux *3	0.0 lux *3	0.0 lux *3	0.0 lux *3	0.0 lux *3	0.1 lux	-	0.0 lux *3	0.01 lux	0.5 lux
(Color)	0.06 lux	0.03 lux	0.4 lux	0.5 lux	0.1 lux	0.1 lux	0.38 lux	0.04 lux	0.05 lux	2.4 lux
Lens	Fisheye f=1.5, F=2.8	2.8 - 12 mm	3 - 9 mm	2.8 mm	2.8mm	3.6 mm	3-12 mm	3.7 - 9 mm	4.7 - 94 mm	4mm
Wide dynamic range	Digital WDR	True WDR	Digital WDR	Digital WDR	Digital WDR	Digital WDR	Digital WDR	Digital WDR	Digital WDR	True WDR
ONVIF	Profile-S	Profile-S	v1.02	Profile-S	Profile-S	Profile-S	v1.02	v1.02	Profile-S	Profile-S

*1 IK10=Vandal Resistant *2 IP66=Water/Dust Resistant *3 With IR on

Recorders



MODEL	EAV16-480	XVSV	XVSE	DVSE	IPSE	NVSPRO
PLATFORM	Embedded Analog (H.264 960H)		Full Hybrid			Network Video Recorder
OVERVIEW						
Image compression	H.264				H.264, MPEG4, MJPEG	
Max number of channels	16				64	
Analog video inputs	16		16			8/16/32
IP video channels ^{*1}	-				Up to 64 ^{*1}	
Display outputs	VGA x 1, HDMI x 1, BNC x 2 ^{*4}		HDMI, display port, DVI-D VGA, RCA ^{*7}			HDMI, display port, DVI-D, VGA ^{*7}
ONVIF	-				Profile-S compliant	
STORAGE						
Storage capacity	12TB	Up to 12TB	Up to 18TB	Up to 24TB	Up to 18TB	Up to 96TB
Maximum number HDD	-	2 Internal	3 Internal	4 Removable	3 Internal	2U: 6, 4U: 16 (Removable)
RAID configuration (optional)	-	-	-	RAID5	-	RAID5
Optical drive	-	DVD/RW	DVD/RW	DVD/RW	DVD/RW	DVD/RW
External storage	2 internal HDD	iSCSI (optional)	-	iSCSI (optional)	-	iSCSI (optional)
FRAME RATES						
Recording rate (PPS)	480fps at 960H and D1 resolution 30fps at 960H and D1 resolution (per channel)	240 at 360x240 120 at 720x240 60 at 720x480	480 at 360x240 240 at 720x240 120 at 720x480	240/480 at 360x240 120/240 at 720x240 60/120 at 720x480		-
Analog live viewing rate (PPS)	480	480	480	240/480		-
IP video throughput (Mbps)	-	200	200	200 (Non-RAID), 400 (RAID5)	200	200 (Non-RAID), 400 (RAID5)
Record on motion	Y				-	
INPUTS/OUTPUTS						
Audio inputs	RCA x 1	16	16	8/16	16 ^{*3}	16 ^{*3}
Sensor/alarm inputs	4	16	16	8/16	-	-
Alarm outputs	1	4	4	8/16	-	-
USB ports	US 2.0 x 2	4x 2.0; 2x 3.0	4x 2.0; 2x 3.0	4x 2.0; 2x 3.0	4x 2.0; 2x 3.0	2U: 3x2.0; 2x3.0; 4U: 4x2.0; 2x3.0
LAN	100/1000 Gigabit Ethernet				Dual 100/1000 Gigabit Ethernet	
REMOTE CLIENTS INCLUDED						
VMS software				Surveillix SCS		
Browser client				Internet Explorer		
Mobile apps				iPad/iPhone/Android		
Cloud-based recorder health				MySurveillix		
SYSTEM						
CPU	-	Intel Dual Core ^{*2}	Intel Dual Core, Core i3 ^{*2}		Intel Core i3 ^{*2}	Intel Core i7
RAM	-	4GB	4GB		4GB	8GB
Recording software	-				Surveillix (included)	
Operating system	Embedded Linux				Windows 7 Embedded	
DIMENSIONS						
Dimensions (h x w x d)	3.5" x 16.5" x 15.75"	5.5" x 19.5" x 13"	5.25" x 17.3" x 21.75"	7" x 17.3" x 21.75"	5.25" x 17.3" x 21.75"	3.3" x 17.2" x 27" (2U) 6.9" x 16.95" x 26.25" (4U)
Rackmount size	1.5U	Desktop Chassis	3U	4U	3U	2U / 4U
Weight	9.6 lbs	30 lbs	30-33 lbs	47-52 lbs	30-33 lbs	48 lbs / 59 lbs
POWER						
Power input	12V, 5A				AC 100-240V (50Hz/60Hz)	
WARRANTY						
Limited warranty	3 year, 1 year replacement				3 years, 1 year advance replacement	

*1 For supported IP camera list visit www.toshibasecurity.com *2 CPU upgrade to Intel Core i7 available *3 On Supported IP cameras via network interface *4 Displays analog video locally only (Main and spot monitor EHV)

*5 eSATA port supports 1 drive only *6 Minimum recommended server specifications *7 Only 2 outputs can be used simultaneously *8 Record on motion with "IKS" series cameras only

IP Network Cameras



MODEL	IK-WF51R	IK-WF51A	IK-WR31A	IK-WD31A	IK-WR14A	IK-WD14A	IK-WR05A	IK-WD05A	IKS-WR7412
	5MP Panoramic (outdoor)	5MP Panoramic (indoor)	3MP vandal (outdoor)	3MP (indoor)	HD 1080p (outdoor)	HD 1080p (indoor)	HD 1080 (outdoor)	HD 1080p (indoor)	HD 1080p (outdoor)
CAMERA									
Image Sensor	1/2.5" CMOS 5MP		1/3" CMOS 3MP		1/2.7 inch CMOS 2MP		1/2.7 inch CMOS 2MP		1/2.8 inch CMOS 2MP
Effective pixels	2560 x 1920		2048 x 1536 (4:3)		1920 x 1080		1920 x 1080		1920 x 1080
Lens	Fisheye f=1.5mm, F=2.8 175° horizontal, vertical Dewarping		Varifocal f=2.8 - 12mm, F=1:1.8 Remote zoom/focus, 90° Hall View 4x optical zoom, 3x digital		Vari-focal f=3 - 9mm, 3x remote zoom, remote focus		Fixed f=2.8mm 4x digital zoom 110° viewing angle		Fixed f=2.8mm, F2.0 90.3° horizontal viewing angle
Min. Illumination	0.6 lux 0.0 lux with IR on		0.03 lux/F1.8 (Night md, LED-OFF Gain 100%, 1/30 sec), 0 lux w/IR on		0.04 lux / F1.2 (Night md, LED-OFF, Gain 100%, 1/30 s), 0 lux IR on		0.5 lux (Color), 0.001 lux (B/W) 0 lux with IR on		0.1 lux 0.0 lux with IR on
IR illuminators	10m x 10m area at 3m range		Adaptive IR LED, 20m range		SRLED*3 20m range		15m range		24 IR (850nm), 50 ft range
FEATURES									
Day/Night	Yes, IR cut filter		Yes, IR cut filter		Yes, electronic		IR cut filter		IR cut filter
Wide Dyn. Range	Digital WDR		True WDR		Digital WDR		Digital WDR		Digital WDR
VIDEO									
Compression	H.264, MPEG4, MJPEG		H.264 Smart Codec, H.264, MJPEG		H.264, MPEG4, MJPEG		H.264, MPEG4, MJPEG		H.264, MJPEG
Resolution	1920², 1536², 1280², 1056², 768², 512², 384², 256², 192²		2048x1536, 1920x1080, 1280x1024, 1280x720, 1024x768, 640x480, 320x240		1920x1080, 1280x1024 1280x720, 1024x768, 640x480, 320x240		1920x1080, 1280x1024 1280x720, 1024x768, 640x480, 320x240		1920x1080, 1280x1024, 1280x720, 720x480, 352x240
Frame rate (max) *1	15fps@5MP, 25fps@1080p (MPEG4) 30fps@1080p (H.264, MJPEG)		20fps@2048x1536, 30fps@1920x1080 60fps@1280x720 (WDR-OFF)		Up to 30 fps @ 1080p		30fps@1920x1080		30fps@1920x1080
Composite output	-		-		NTSC and PAL		Yes		-
AUDIO									
Audio In/Out *2	MIC IN (plug-in 3.3V, 200kΩ), LINE OUT (1 Vrms) G.726, G711		MIC IN (plug-in 3.3V, 200kΩ) LINE OUT (1 Vrms)	Built-in MIC, MIC In (plug-in 3.3V, 200kΩ), Line Out (1 Vrms)	MIC In (plug-in 3.3V, 200kΩ) LINE OUT (1 Vrms)	Built-in MIC, MIC In (plug-in 3.3V, 200kΩ), Line Out (1 Vrms)	-		-
NETWORK									
ONVIF	Profile-S		Profile-S (test tool v14.06)		Ver. 1.02		Profile S		Profile S
INTERFACE									
Digital In/out	1 IN/1 OUT		1 IN/1 OUT		1 IN/1 OUT		1 IN		-
SD card slot	MicroSD/SDHC/SDXC 64GB max		MicroSD 64GB max		Yes, max 32GB		Micro SD/SDHC, max 32GB		Micro SD/SDHC, max 32GB
GENERAL									
Dimensions`	2" (H) x 6.3" (Dia) (51mm x 160mm)	1.5" (H) x 6.3" (Dia) (39mm x 160mm)	4.5"(H) x 6.8"(D) (115mm x 173mm)	4.3"(H) x 6.3"(D) (109mm x 159mm)	6.8" (H) x 4.5" (D) (173mm x 115mm)	6.3" (H) x 4.3"(D) (160mm x 109mm)	3.7"(H) x 5.24" (D) (94mm x 133mm)	3.15" (H) x 4.33" (D) (80mm x 110mm)	3.125" (H) x 4.625" (D) (79.4mm x 117.5mm)
Weight	1.75 lbs (794g)	1.3 lbs (589g)	2.89 lbs (1310 g)	1.67 lbs (758 g)	2.98 lbs (1350g)	1.83 lbs (830g)	1.1 lbs (500g)		0.73 lbs (330g)
Power Requirements	12V DC ±10% 802.3af PoE, 802.3at PoE+		12V DC±10% 802.3af PoE		12V DC ± 10%, 24VAC± 10% 60 Hz 802.3af class 3 PoE		12V DC 802.3af PoE		802.3af PoE
Power consumption	22W		12V DC/2.1A		15.4W max		3.84W max		5.8W
Operation temp.	PoE: 14°F to 122°F PoE+: -22°F to 122°F 12V: -22°F to 122°F	14°F to 122°	PoE: -4F to 122°F 12V DC: -22° to 122°F	14°F to 122°F (-10°C to 50°C)	PoE: -22°F to 122°F 12V DC and 24V AC: -13°F to 122°F	32°F to 122°F (0°C to 50°C)	-4°F to 122°F (-20°C to 50°C)	14°F to 122°F (-10°C to 50°C)	14°F to 122°F (-10C to 50°C)
Environmental	IP66, EN50155 (rail)	-	IK10, IP66	-	IK10, IP66	-	IK10, IP66	-	IP66
Warranty	2 years parts and labor (all Toshiba IP cameras)								

*1: Varies in accordance with the object, image quality, network environment and performance of the client used. *2: Sound quality varies depending on the condition of the network. *3: SRLED is Single Reflection LED

IP Network Cameras



MODEL	IKS-WD6112	IK-WR04A	IK-WD04A	IK-WB81A	IKS-WP8203R	IKS-WP8103	IKS-WR7022
	Low Profile HD 1080p (indoor)	720p (outdoor)	720p (indoor)	HD 1080p Bullet	HD 1080p Outdoor PTZ	HD 1080p Indoor PTZ	HD 1080p PT dome
CAMERA							
Image Sensor	1/2.8 inch CMOS 2MP	1/4 inch CMOS		1/2.7 inch CMOS 2MP	1/2.8 inch CMOS 2MP		1/2.8 inch CMOS 2MP
Effective pixels	1920 x 1080	1280 x 800		1920 x 1080	1920 x 1080		1920 x 1080
Lens	Fixed f=3.6, F=1.8 8x digital zoom	Vari-focal f=3-12mm 4x optical zoom		Vari-focal f=3.7- 9mm 3x optical zoom 4x digital zoom	Autofocus f=4.7- 94mm 20x optical zoom 360° Pan/Tilt		f=4mm, Fixed 1.6 Digital zoom 350° Pan, 90° Tilt
Min. Illumination	0.1 lux @ F1.8, 30 IRE	0.38 lux/F1.4		0.04 lux/F1.2	0.05 lux (color) 0.01 lux (B&W) @ F1.6		2.4 lux (color) 0.5 lux (B&W)
IR illuminators	-	-		SRLED *3 30m range	-		-
FEATURES							
Day/Night	Yes, electronic	Yes, electronic		Yes, IR cut filter	Yes, IR cut filter		Digital
Wide Dyn. Range	Digital WDR	Digital WDR		Digital WDR	Digital WDR		True WDR
VIDEO							
Compression	H.264, MJPEG	H.264, MPEG4, MJPEG		H.264, MPEG4, MJPEG	H.264, MJPEG		H.264, MPEG4, MJPEG
Resolutions	1920x1080, 1280x1024, 1280x720, 720x480, 352x240	1280x800, 640x400, 320x200, 76x144		1920x1080, 1600x904, 1360x768 1280x720, 640x360, 176x144	1920x1080, 1280x1024, 1024x768, 1280x720, 800x600, 720x480, 640x480, 352x240		1920x1080, 1280x1024, 1280x720 1024x768, 800x600, 640x480, 352x240
Frame rate (max) *1	30fps@1920x1080	30fps@1280x800		30fps@1920x1080	30 fps@ all resolutions		30 fps@ all resolutions
Composite output	-	Yes		Yes	-		-
AUDIO							
Audio In/Out *2	Built in MIC (G.726, G.711)	-		MIC In (plug-in 3.3V, 200kΩ) LINE OUT (1 Vrms)	1 IN/1 OUT G.726, G711		-
NETWORK							
ONVIF	Profile S	Ver. 1.02		Ver. 1.02	Profile S		Profile S
INTERFACE							
Digital In/Out	-	1 IN		1 IN/1 OUT	4 IN/2 OUT		1 IN/1 OUT
SD card slot	MicroSD, Max 16GB	Yes, max 32GB		SD/SDHC, max 32GB	MicroSD/SDHC		MicroSD 16GB max
GENERAL							
Dimensions	1.75" (H) x 4.625" (D) (44.45mm x 117.5mm)	3.7" (H) x 5.24" (D) (94mm x 133mm)	3.15" (H) x 4.33" (D) (80mm x 110mm)	7.83" (H) x 3.19" (Dia) (199mm x 81mm)	11.1" (H) x 7.5" (Dia) (282.1mm x 192mm)	8.625" (H) x 5.875" (Dia.) (219mm x 150mm)	2.9" (H) x 4.9" (Dia) (74mm x 125mm)
Weight	0.4 lbs (180g)	1.3 lbs (589g)	1.1 lbs (500g)	2.86 lbs (1.3kg)	5.11 lbs (2.32 kg)	5.11 lbs (2.32 kg)	0.97 lbs (439g)
Power Requirements	802.3af PoE	12V DC ± 10 % 802.3af class 3 PoE		12V DC ± 10%, 24VAC ± 10% 60Hz 802.3af class 3 PoE	24VAC 802.3af PoE+	24VAC 802.3af PoE+	12VDC 802.3af PoE
Power consumption	3.5W	3.8W		12V DC / 0.8A, 24V AC / 0.8A	65W max (w/heater or fan)	20W max	8.2W max
Operation temp.	14°F to 122°F (-10C to 50°C)	-22°F to 122°F (-30°C to 50°C)	14°F to 122°F (-10°C to 50°C)	-22°F to 122°F (-30°C to 50°C)	-40°F to 122°F (-40°C to 50°C)	32°F to 122°F (0°C to 50°C)	14°F to 122°F (-10C to 50°C)
Environmental	-	IK10, IP66	-	IP66	IP66	-	IP66
Warranty	2 years parts and labor (all Toshiba IP cameras)						

*1: Varies in accordance with the object, image quality, network environment and performance of the client used. *2: Sound quality varies depending on the condition of the network. *3: SRLED is Single Reflection LED

Analog Cameras



MODEL	IKS-R307	IKS-D207
	960H Dome (outdoor)	960H Dome (indoor)
CAMERA		
Image sensor	1/3" CCD	
Angle of view	28° - 91°	
TVL	650 TVL	
Lens	Vari-focal f= 2.8 - 12mm Auto iris, 4x zoom	
Min. illumination	0.1 lux (color) 0.05 lux (B&W), 40 IRE	
IR illuminators	24 LEDs, 50 ft range	
S/N ratio	>52db (AGC off)	
FEATURES		
Day/Night	True D/N	
Wide Dyn. Range	True WDN	
White balance	Manual, AWB, ATW (1800K - 10500K)	
Gain (AGC)	Auto	
Tilt/Rotate	tilt=87°, rotate=360°	
BLC	BLC, HLC, Off	
Sync	Internal/Line lock	
VIDEO		
Output	1.0Vpp 75 Ohm BNC unbalanced	
Format	NTSC	
INTERFACE		
Video connectors	BNC, service monitor jack	
GENERAL		
Dimensions	5.13" x 5.925" (Dia)	3.97" x 5.125" (Dia)
Weight	1.8 lbs	1.1 lbs
Power requirements	12VDC/24VAC	
Power consumption	7.2W	5.4W
Operation temp.	-49° F to 122°F	14°F to 122°F
Environmental	IK10	-
Warranty	2 years parts and labor	

Camera Accessories

Toshiba offers a full range of accessories to maximize the performance and value of its analog and IP cameras.






Visit www.toshibasecurity.com/products/accessories to view by selecting the model number from the drop down list and then clicking on the search button. Below are our most popular camera solutions.

Popular Mounting Solutions for the IK-WR14A & IK-WR31A






SURFACE	PART NUMBER(S)
	<p>1. JK-WM12 + 2. JK-PHO14 OR 3. JK-WM14</p>
	<p>1. JK-CMA12 + 2. JK-PHO14 + 3. JK-WM12</p>
	<p>1. JK-PMA12 + 2. JK-PHO14 + 3. JK-WM12</p>
	<p>1. JK-PHO14 + 2. JK-PMH12 OR 3. JK-PMP12 + (JK-PHO14 + JK-PMH12)</p>
	<p>1. JK-JCB12</p>

In the charts below “OR” means that you can choose one or the other accessory to complete the mount, while “+” means you must use the accessories together. For example, to install a Corner Mount for the IKS-WP8103 you would use the JK-510C plus either the JK-510W or the JK-510WL. To install a corner mount for the IK-WR14A, you must use the JK-CMA14 plus the JK-PHO14 and the JK-WM14.





Popular Mounting Solutions for the IK-WF51A & IK-WF51R

SURFACE	PART NUMBER(S)	
Wall	1. JK-WM12 + 2. JK-PHO14	
Corner	1. JK-CMA12 + 2. JK-PHO14 + 3. JK-WM12	
Pole	1. JK-PMA12 + 2. JK-PHO14 + 3. JK-WM12	
Pendant	1. JK-PHO14 + 2. JK-PMH12 OR 3. JK-PMP12	
Adapter Plate	1. JK-JBA3 (IK-WF51A only)	

Popular Mounting Solutions for the IKS-WP8103

SURFACE	PART NUMBER(S)	
In-Ceiling	1. JK-MFMK	
Wall	1. JK-510W OR 2. JK-510WL	
Corner	1. JK-510C + 2. JK-510W OR 3. JK-510WL	
Pole	1. JK-510PML + 2. JK-510W OR 3. JK-510WL	
Pendant	1. JK-510P25 OR 2. JK-510P50	

Popular Mounting Solutions for the IKS-WP8203R

SURFACE	PART NUMBER(S)	
Wall	1. JK-510W OR 2. JK-510WL	
Corner	1. JK-510C + 2. JK-510W OR 3. JK-510WL	
Pole	1. JK-510PML + 2. JK-510W OR 3. JK-510WL	
Pendant	1. JK-510P25 OR 2. JK-510P50	

Mounting for the IKS-WD6112 and IKS-WR7412

SURFACE	PART NUMBER(S)	
Pendant	1. JK-CA6000PMK	

Toshiba Authorized Dealer Network

A fixture in the surveillance industry since 1987, Toshiba Surveillance & IP Video Products Group markets a wide range of video surveillance solutions including network-based IP cameras, analog cameras, video servers, embedded video recorders, software, and accessories. Our mission is to provide superior technology, service and value to surveillance professionals and to move the industry forward by consistently introducing innovative products into the marketplace.

Toshiba products are sold through a nationwide network of reseller partners that are carefully selected, providing unparalleled technical, sales and service support. You can be assured that our reseller partners are thoroughly and professionally trained on Toshiba products. Our dealers have contributed greatly to our success and we place our complete trust and confidence in them.



Partnering with Toshiba is Smart Business. Here's why.

On-Site Commissioning Service: At no cost to you, a Toshiba Technical Specialist will visit your installed IP video surveillance site and leverage their expertise to optimize Toshiba IP Video equipment for the most reliable, highest quality performance. The Toshiba Specialist will also provide end-user training.

MySurveillix Surveillance Monitoring: This web-based service manages the health of an end-user's surveillance system. It reports on the health of all systems and takes day & night thumbnail images daily to ensure all cameras are working properly.

24/7 Tech Support: Emergencies happen, and usually at the worst times. That is why Toshiba's technical support department offers around-the-clock callback service.

Virtual Installer: A skilled tech support representative will walk you through your Toshiba equipment installation for the fastest, most trouble-free deployment.

Low total cost of ownership: No annual software fees, plus unlimited free remote users means your total cost of ownership won't increase every year.